

AN EASY DOSE RATE GUIDE FOR THE USE OF 'abilox®' PIGMENTS IN PREMIXED CONCRETE

FOR A DOSE RATE OF

ABILITY BUILDING CHEMICALS CO

Subsidiary of Australian Oxides Pty Ltd 133-135 Northern Road, West Heidelberg, Vic, 3081, Australia Tel: (03) 9457 6488 Fax: (03) 9458 4683

> 'abilox®' **BLACK CAF-X2**

Sample Biscuit Dose Rate: 8.3% in

off-white cement (by weight) (110)

INDICATION OF CURED SHADE ONLY.
IN PRACTISE FINAL SHADE TAKES TYPICALLY 28 DAYS TO ACHIEVE

ABILITY BUILDING CHEMICALS CO

Subsidiary of Australian Oxides Pty Ltd 133-135 Northern Road, West Heidelberg, Vic, 3081, Australia Tel: (03) 9457 6488 Fax: (03) 9458 4683

'abilox®' BLACK CAF-X2

Sample Biscuit

Dose Rate: 8.3% in grey cement (by weight)

INDICATION OF CURED SHADE ONLY.

IN PRACTISE FINAL SHADE TAKES TYPICALLY 28 DAYS TO ACHIEVE

You will need to purchase/order/specify:

2 x 12.5kg bags per cubic metre

PLEASE NOTE: ON PRINTED COLOUR SPECIFIER

gc means: grey cement

owc means: off white cement

PLEASE NOTE:

On the 'biscuit' label it specifies what type of cement needs to be used: either grey cement or off white cement

FOR A DOSE RATE OF

ABILITY BUILDING CHEMICALS CO

Subsidiary of Australian Oxides Pty Ltd 133-135 Northern Road, West Heidelberg, Vic, 3081, Australia Tel: (03) 9457 6488 Fax: (03) 9458 4683

'abilox®' **BLACK CAF-X2**

Sample Biscuit

Dose Rate: 4.15% in

off-white cement (by weight) (111)

INDICATION OF CURED SHADE ONLY.
IN PRACTISE FINAL SHADE TAKES TYPICALLY 28 DAYS TO ACHIEVE

ABILITY BUILDING CHEMICALS CO

Subsidiary of Australian Oxides Pty Ltd 133-135 Northern Road, West Heidelberg, Vic, 3081, Australia Tel: (03) 9457 6488 Fax: (03) 9458 4683

'abilox®' **BLACK CAF-X2**

Sample Biscuit

Dose Rate: 4.15% in

grey cement (by weight)

INDICATION OF CURED SHADE ONLY.
IN PRACTISE FINAL SHADE TAKES TYPICALLY 28 DAYS TO ACHIEVE

(6)

You will purchase/order/specify:

1 x 12.5kg bag per cubic metre

PLEASE NOTE:

ON PRINTED COLOUR SPECIFIER

gc means: grey cement

owc means: off white cement

PLEASE NOTE:

On the 'biscuit' label it specifies what type of cement needs to be used: either grey cement or off white cement